

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz single side cooled, T _{HS} =55°C	150			177	A
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz single side cooled, T _{HS} =90°C	150			122	A
V _{RRM}	Repetitive peak reverse voltage	V _{RRM} tp=10ms V _{RSM} = V _{RRM} +100V	150	100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			16	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			2.2	KA
I ² T	I ² T for fusing coordination	V _R =0.6V _{RRM}				24	A ² s*10 ³
V _{FO}	Threshold voltage		150			1.56	V
r _F	Forward slop resistance					1.34	mΩ
V _{FM}	Peak on-state voltage	I _{TM} =300A	150			2.0	V
I _{rm}	Reverse recovery current	I _{TM} =300A, tp=1000μs, di/dt=-20A/μs, V _R =50V	150			40	A
t _{rr}	Reverse recovery time					4	μs
Q _{rr}	Recovery charge					80	μC
R _{th(j-h)}	Thermal resistance Junction to heatsink	At 180° sine single side cooled Clamping torque 17 N·m				0.25	°C /W
F _m	Mounting torque			13		19	N·m
T _{stg}	Stored temperature			-40		160	°C
Outline	D2						

Outline

